

VASCONY®

WORKTOPS



The mark of
responsible forestry

All our products can be supplied
as FSC® certified, on request

www.vascony.ro

THE WHOLE
IS MORE THAN
THE SUM
OF ITS PARTS ...
Aristotel





Thanks to the production techniques made use of we ensure that the final product is of the best quality and absolute beauty.

The finger joint system is a guarantee for the stability of the product made of oak staves.

We can produce unfinished and finished worktops, depending on your requests.





FINGER JOINT WORKTOPS SPECIFICATIONS

Features:

Thickness-

18/19/20/26/27/32/38/40 mm

Standard Dimensions:

Width-

600/620/650/720/960/1220 mm

Length-

2000/3000/4000/4200 mm

Quality grade:

AB/BC

Moisture content:

8%(+/-2%) KD

Joint Style:

Visible finger joints on the long edge

Glue:

Type D3

FINGER JOINT WORKTOPS SPECIFICATIONS

Finger joint material:

Finger jointed staves from 150 mm in length, standard stave width 40+/-2 mm or customized stave width

Surface treatments:

Panels can be oiled

Packing:

Each board will be individually shrink-wrapped and packaged in strong pallet with corner protector

Certificate:

FSC

Types of essences:

Oak, dark oak, beech, ash and cherry





QUALITY DESCRIPTION

A/B grade:

- ▶ a few pin knots of 5 mm diameter are allowed on A face, 25 mm knots are allowed on back side;
- ▶ black knots are allowed on A face – maximum 10 mm;
- ▶ natural color differences are allowed;
- ▶ inbark is allowed on the back side;
- ▶ knots can be repaired with matching color filler.



QUALITY DESCRIPTION

B/C grade :

- ▶ on A face are allowed knots up to 25 mm, sound sapwood, maximum 50% of the lamellas;
- ▶ on B face are allowed knots up to 40 mm, sound sapwood;
- ▶ natural color differences are allowed;
- ▶ knots can be repaired with matching color filler.





VASCONY PROD SRL

Ulmi, Dambovita

Romania

Mobile Phone: 0040 724 383 818

Tel./Fax: 0040 245 210 977

E-mail: vascony.office@gmail.com

www.vascony.ro